DEVELON

Europe

Full liner

MINI EXCAVATORS

		DX10Z-7	DX17Z-7
Operating weight	kg	1165	1850
Engine power	hp/kW @ rpm	10.33/7.4 @ 2050	16.5/11.9 @ 2400
Bucket capacity (SAE)	m^3	0.024	0.04

DX50Z-7	DX55R-7	DX62R-7
5438	5740	6216
48.8/36.6 @ 2200	48.8/36.6 @ 2200	59.4/44.3 @ 2300
0.16	0.16	0.175

		DX10Z-7	DX17Z-7	DX19-7	DX27Z-7
Operating weight	kg	1165	1850	1885	2705
Bucket capacity (SAE)	m^3	0.024	0.04	0.04	0.08
Travel speed	km/h	3.4 - 1.7	2.21 - 4.09	2.06 - 3.73	2.5 - 4.3
Engine model	-	Kubota D722	Kubota D902	Kubota D902	Develon D17
Power	hp/kW @ rpm	10.33/7.4 @ 2050	16.5/11.9 @ 2400	16.5/11.9 @ 2400	24.8/18.4 @ 2400
Emission standard	-	Stage V	Stage V	Stage V	Stage V
Digging reach	mm	3400	3910	3940	4655
Digging depth	mm	1815	2240	2340	2645
Digging height	mm	2205	3730	3470	2935
Length	mm	3010	3531	3837	4191
Width	mm	1100 (730)	1290 (994)	1290 (994)	1550
Height	mm	2220	2320	2299	2275

DX19-7	DX27Z-7	DX35Z-7
1885	2705	3499
16.5/11.9 @ 2400	24.8/18.4 @ 2400	24.8/18.4 @ 2400
0.04	0.08	0.11

DX63-7	DX85R-7
6218	9520
59.4/44.3 @ 2100	65/48.5 @ 2100
0.175	0.28

DX35Z-7	DX50Z-7	DX55R-7	DX62R-7	DX63-7	DX85R-7
3499	5438	5740	6216	6218	9520
0.11	0.16	0.16	0.175	0.175	0.28
2.6 - 4.7	2.6 - 4.4	2.6 - 4.4	2.8 - 4.7	2.8 - 4.7	2.7 - 4.7
Develon D17	Develon D18	Develon D18	Develon D24	Develon D24	Develon D24
24.8/18.4 @ 2400	48.8/36.4 @ 2200	48.8/36.4 @ 2200	65/44.3 @ 2300	65/44.3 @ 2300	65/48.5 @ 2100
Stage V	Stage V	Stage V	Stage V	Stage V	Stage V
5355	5945	6090	6610	6440	7530
3275	3480	3630	4095	4095	4665
3580	5575	5680	6025	6025	7035
4760	5386	5400	5631	5571	6265
1700	1980	1980	1980	1980	2250
2479	2575	2575	2575	2575	2657

WHEELED EXCAVATORS

		DX57W-7	DX100W-7
Operating weight	kg	5800	10700
Engine power	hp/kW @ rpm	52.3/42.5 @ 2400	100/75 @ 2000
Bucket capacity (SAE)	m^3	0.175	0.3

DX165W-7	DX170W-7
17400 - 18900	17700 - 19300
137/102 @ 2200	152/113 @ 2000
0.7	0.75

		DX57W-7	DX100W-7	DX140W-7
Operating weight	kg	5800	10700	15800 - 17000
Bucket capacity (SAE)	m^3	0.175	0.3	0.6
Travel speed	km/h	10 - 30	5.4 - 37.4	3.5 - 37
Engine model	-	Develon D24	Develon D34	Develon DL06V
Power	hp/kW @ rpm	52.3/42.5 @ 2400	100/75 @ 2000	137/103 @ 2000
Emission standard	-	Stage V	Stage V	Stage V
Digging reach	mm	6108	7820	7585
Digging depth	mm	3495	4245	4490
Digging height	mm	5976	8265	8195
Length	mm	5896	5713	8043
Width	mm	1947	2450	2495
Height	mm	2861	3011	3052
Arm length	mm	1600	2250	2100

DX140W-7	DX160W-7
15800 - 17000	17500 - 18100
137/103 @ 2000	137/103 @ 2000
0.6	0.7

DX190W-7	DX210W-7
18320 - 20410	21900 - 23000
174/130 @ 1900	189/141 @ 1900
0.8	0.9

DX160W-7	DX165W-7	DX170W-7	DX190W-7	DX210W-7
17500 - 18100	17400 - 18900	17700 - 19300	18320 - 20410	21900 - 23000
0.7	0.7	0.75	0.8	0.9
3.5 - 37	3 - 34	3.0 - 37	3.5 - 37	4.0 - 35
Develon DL06V	Perkins 1204J	Develon DL06V	Develon DL06V	Develon DL06V
137/103 @ 2000	137/102 @ 2200	152/113 @ 2000	174/130 @ 1900	189/141 @ 1900
Stage V	Stage V	Stage V	Stage V	Stage V
8235	8235	8875	9255	9980
5020	5020	5315	5725	6160
8850	8850	9140	9440	10140
8205	8205	8644	8867	9477
2495	2490	2530	2530	2530
3052	3102	3087	3131	3155
2500	2500	2500	2600	3000

CRAWLER EXCAVATORS

		DX140LCR-7	DX140LC-7
Operating weight	kg	15500	14400
Engine power	hp/kW @ rpm	115/86 @ 2000	115/86 @ 2000
Bucket capacity (SAE)	m^3	0.75	0.75

DX210LC-7	DX210NLC-7
21700	21700
166/124 @ 1800	166/124 @ 1800
1.2	1.2

		DX140LCR-7	DX140LC-7	DX160LC-7HT
Operating weight	kg	15500	14400	16800
Bucket capacity (SAE)	m^3	0.75	0.75	0.8
Travel speed	km/h	2.9 - 4.7	2.9 - 4.7	2.3 - 3.7
Engine model	-	Develon G2 D34	Develon G2 D34	Develon G2 D34
Power	hp/kW @ rpm	115/86 @ 2000	115/86 @ 2000	115/86 @ 2000
Emission standard	-	Stage V	Stage V	Stage V
Digging reach	mm	8285	8285	8285
Digging depth	mm	5485	5635	5635
Digging height	mm	9265	8660	8660
Length	mm	7360	7685	7685
Width	mm	2590	2590	2590
Height	mm	2835	2785	2785
Arm length	mm	2500	2500	2500

DX160LC-7HT	DX210-7
16800	21300
115/86 @ 2000	166/124 @ 1800
0.8	1.1

DX225LC-7X	DX235LC-7
23300	23000
174/129 @ 1800	174/129 @ 1800
1.3	1.4

DX210-7	DX210LC-7	DX210NLC-7	DX225LC-7X	DX235LC-7
21300	21700	21700	23300	23000
1.1	1.2	1.2	1.3	1.4
3.2 - 5.9	3.2 - 5.9	3.2 - 5.9	3.1 - 5.5	3.0 - 5.3
Develon DL06V	Develon DL06V	Develon DL06V	Develon DL06V	Develon DL06V
166/124 @ 1800	166/124 @ 1800	166/124 @ 1800	174/129 @ 1800	174/129 @ 1800
Stage V	Stage V	Stage V	Stage V	Stage V
9535	9535	9535	9865	9895
6270	6270	6270	6590	6595
9330	9330	9330	9620	9555
9445	9445	9445	9570	9522
2800	2990	2540	2990	2990
3139	3139	3139	3005	3139
2600	2600	2600	2900	2900

CRAWLER EXCAVATORS

		DX235LCR-7	DX245NHD-7
Operating weight	kg	24300	25100
Engine power	hp/kW @ rpm	174/129 @ 1800	174/129 @ 1800
Bucket capacity (SAE)	m^3	1.4	1.3

DX350LC-7	DX380LC-7
40200	43500
285.6/213 @ 1800	326/240 @ 1800
1.85	2.0

		DX235LCR-7	DX245NHD-7	DX255LC-7
Operating weight	kg	24300	25100	25700
Bucket capacity (SAE)	m^3	1.4	1.3	1.5
Travel speed	km/h	3.2 - 5.8	3.0 - 5.3	3.2 - 5.6
Engine model	-	Develon DL06V	Develon DL06V	Develon DL06V
Power	hp/kW @ rpm	174/129 @ 1800	174/129 @ 1800	189/141.3 @ 1900
Emission standard	-	Stage V	Stage V	Stage V
Digging reach	mm	9830	9465	10175
Digging depth	mm	6680	6095	6810
Digging height	mm	10805	9450	9705
Length	mm	8970	9566	10080
Width	mm	2990	2540	3000 - 3200
Height	mm	3123	3190	3200
Arm length	mm	2900	2400	3000

DX255LC-7	DX300LC-7
25700	31500
189/141.3 @ 1900	271/202 @ 1800
1.5	1.7

DX420LC-7	DX490LC-7
43500	50400
344.4/257 @ 1800	394/294 @ 1800
2.2	3.0

DX300LC-7	DX350LC-7	DX380LC-7	DX420LC-7	DX490LC-7
31500	40200	43500	43500	50400
1.7	1.85	2.0	2.2	3.0
3.0 - 5.5	3.5 - 5.7	3.0 - 5.4	3.2 - 5.3	3.2 - 5.6
Develon DL08V	Develon DL08V	Scania DC09	Scania DC13	Scania DC13
271/202 @ 1800	285.6/213 @ 1800	326/240 @ 1800	344.4/257 @ 1800	394/294 @ 1800
Stage V	Stage V	Stage V	Stage V	Stage V
10725	10980	11170	11430	12125
7305	7540	7415	7635	7790
10325	10325	10435	10615	11050
10605	11350	11285	11740	12230
3000 - 3200	3000 - 3280	3000 - 3350	3350	2990 - 3490 3340 - 3900
3050	3390	3415	3355	3350
3100	3200	3200	3250	3350

CRAWLER EXCAVATORS

DX530LC-7

Operating weight	kg	52900
Engine power	hp/kW @ rpm	394/294 @ 1800
Bucket capacity (SAE)	m^3	3.3

DX800LC-7

79500
539/402 @ 2100
2.9 - 4.8

DX1000LC-7

99500
629/469 @ 2000
3.2 - 5.6

		DX530LC-7	DX800LC-7	DX1000LC-7
Operating weight	kg	52900	79500	99500
Bucket capacity (SAE)	m^3	3.3	4.6	6.8
Travel speed	km/h	3.2 - 5.6	2.9 - 4.8	3.2 - 5.6
Engine model	-	Scania DC13	Perkins 2506	Perkins 2806
Power	hp/kW @ rpm	394/294 @ 1800	539/402 @ 2100	629/469 @ 2000
Emission standard	-	Stage V	Stage V	Stage V
Digging reach	mm	10735	11250	12430
Digging depth	mm	6755	6685	7260
Digging height	mm	9630	10700	12425
Length	mm	11530	12230	11530
Width	mm	2990 - 3490 3340 - 3900	3400 - 4000	3440 - 4200
Height	mm	3350	3540	3615
Arm length	mm	2900	3350	2900

WHEEL LOADERS

		DL200-7
Operating weight	kg	12047
Engine power	hp/kW @ rpm	144/106 @ 2200
Bucket capacity (SAE)	m^3	2.0

DL220-7	DL250-7
13300	13900
160/119 @ 2100	172/128 @ 2100
2.3	2.5

		DL200-7	DL220-7	DL250-7
Operating weight	kg	12047	13300	13900
Bucket range (GP)	m^3	1.9 - 2.2	2.2 - 2.5	2.4 - 2.7
Engine model	-	Perkins 1204J	Develon DL06	Develon DL06
Power	hp/kW @ rpm	144/106 @ 2200	160/119 @ 2100	172/128 @ 2100
Emission standard	-	Stage V	Stage V	Stage V
Bucket capacity (SAE)	m^3	2.0	2.3	2.5
Tipping load (straight/full turn at 40°)	kg	10124/8933	10652/9383	11015/9696
Max. dump height on pivot	mm	3716	3853	3853
Breakout force	kN	98	97	116
Maximum speed	km/h	40	40	40
Turning radius at bucket	mm	5414	6016	6115
Tires	-	20.5 R25	20.5 R25	20.5 R25
Length	mm	7208	7458	7487
Width – at tires edge	mm	2539	2539	2539
Height	mm	3313	3313	3313

WHEEL LOADERS

		DL280-7	DL320-7
Operating weight	kg	15562	19493
Engine power	hp/kW @ rpm	190/141 @ 2000	271/202 @ 1800
Bucket capacity (SAE)	m^3	2.8	3.3

DL420CVT-7	DL480-7
23990	26444
326/240 @ 1800	345/257 @ 1800
4.5	4.8

		DL280-7	DL320-7	DL380-7
Operating weight	kg	15562	19493	20269
Bucket range (GP)	m^3	2.7 - 3.1	3.3 - 3.8	3.7 - 4.1
Engine model	-	Develon DL06	Develon DL08	Develon DL08
Power	hp/kW @ rpm	190/141 @ 2000	271/202 @ 1800	271/202 @ 1800
Emission standard	-	Stage V	Stage V	Stage V
Bucket capacity (SAE)	m^3	2.8	3.3	3.7
Tipping load (straight/ full turn at 40°)	kg	12247/ 10765	15948/ 14079	16248/ 14341
Max. dump height on pivot	mm	3934	4175	4175
Breakout force	kN	140	170	181
Maximum speed	km/h	40	40	40
Turning radius at bucket	mm	6182	6748	6797
Tires	-	20.5 R25	23.5 R25	23.5 R25
Length	mm	7669	8530	8530
Width – at tires edge	mm	2550*	2845	2845
Height	mm	3360	3511	3511

* narrow rims

DL380-7	DL420-7
20269	23990
271/202 @ 1800	345/257 @ 1800
3.9	4.5

DL550-7	DL580-7
33209	34311
380/283 @ 1800	400/294 @ 1800
5.4	6.0

DL420-7	DL420CVT-7	DL480-7	DL550-7	DL580-7
23990	23990	26444	33209	34311
4.3 - 5.0	4.3 - 5.0	4.8 - 5.3	5.4 - 5.9	6.0 - 6.6
Scania DC13	Scania DC09	Scania DC13	Scania DC13	Scania DC13
345/257 @ 1800	326/240 @ 1800	345/257 @ 1800	380/283 @ 1800	400/294 @ 1800
Stage V	Stage V	Stage V	Stage V	Stage V
4.3	4.3	4.8	5.4	6.0
19351/ 17071	19351/ 17071	20717/ 18282	24830/ 21897	27355/ 24315
4265	4265	4519	4806	4996
183	183	224	230	264
40	40	40	40	40
7065	7065	7352	7573	7596
26.5 R25	26.5 R25	26.5 R25	29.5 R25	29.5 R25
9138	9138	9454	9885	10059
2982	2982	3095	3289	3289
3660	3660	3635	3863	3863

COMPACT WHEEL LOADERS

		DL60-7
Operating weight	kg	3750
Engine power	hp/kW	66/48.5
Bucket capacity (SAE)	m^3	0.6

DL80TL-7
5200
75/55
0.9

		DL60-7	DL65-7
Operating weight	kg	3750	3650
Bucket range (GP)	m^3	0.4 - 1.2	0.4 - 1.2
Engine model	-	Kubota V2403	Kubota V2403
Power	hp/kW	66/48.5	66/48.5
Emission standard	-	Stage V	Stage V
Bucket capacity (SAE)	m^3	0.6	0.6
Tipping load (straight/full turn at 40°)	kg	2160/1840	2325/1985
Max. lifting height (pallet forks)	mm	3290	2670
Maximum speed	km/h	30	30
Tires	-	11.5/80 - 15.3	11.5/80 - 15.3
Length	mm	4660	4595
Width – at tires edge	mm	1340	1340
Height	mm	2275	2275

DL65-7	DL80-7
3650	5200
66/48.5	75/55
0.6	0.9

DL85-7
5100
75/55
0.9

DL80-7	DL80TL-7	DL85-7
5200	5200	5100
0.6 - 2.0	0.6 - 2.0	0.6 - 2.0
Kubota V3307	Kubota V3307	Kubota V3307
75/55	75/55	75/55
Stage V	Stage V	Stage V
0.9	0.9	0.9
2965/2480	2430/2050	3220/2735
3500	4350	2850
20 - 35	20 - 35	20 - 35
11.5/80 - 15.3	11.5/80 - 15.3	11.5/80 - 15.3
5002	5310	4993
1460	1460	1460
2523	2523	2523

ARTICULATED DUMP TRUCKS

Maximum payload	kg
Maximum power (ISO 3046)	kW @ rpm
Body capacity heaped (without/with tailgate)	m^3

DA45-7
41000
368 @ 2100
24.4/26.1

		DA30-7
Speeds - forward	km/h	6 - 8 - 11 - 16 - 23 - 32 - 45 - 55
Speeds - reverse	km/h	6 - 8 - 11 - 16
Engine model	-	Scania DC9
Power	kW @ rpm	276 @ 2100
Emission standard	-	Stage V
Transmission model	-	ZF 8 EP320
Weight empty front/rear axle	kg	12700/10500
Weight loaded front/rear axle	kg	15872/35328
Net weight	kg	23200
Length	mm	9534
Width	mm	2967
Total height	mm	3560

DA30-7

28000
276 @ 2100
16.8/17.8

DA45-7 4X4

41000
368 @ 2100
25.7

DA45-7	DA45-7 4X4
5 - 8 - 11 - 16 - 23 - 32 - 45 - 55	5 - 8 - 11 - 16 - 23 - 32 - 45 - 55
5 - 8 - 11 - 16	5 - 8 - 11 - 16
Scania DC13	Scania DC13
368 @ 2100	368 @ 2100
Stage V	Stage V
ZF 8 EP420	ZF 8 EP420
14200/15900	14500/16000
22041/49059	22165/49335
30100	30500
10590	10187
3475	3990
3850	3850

SPECIAL APPLICATION RANGE

SLR and Semi-SLR		DX225LC-7 SLR
Operating weight	kg	24600
Bucket capacity (SAE)	m^3	0.39
Travel speed	km/h	3.1 - 5.5
Engine model	-	Develon DL06V
Power	hp/kW @ rpm	174/129 @ 1800
Emission standard	-	Stage V
Digging reach	mm	15365
Digging depth	mm	11660
Digging height	mm	13045
Length	mm	12390
Width	mm	3190
Height	mm	3385

	DX300LC-7 SLR	DX530LC-7 Semi SLR	DX530LC-7 SLR
	33000	51900	52200
	0.64	1.27	0.92
	3.0 - 5.5	3.2 - 5.6	3.2 - 5.6
	Develon DL08P	Scania DC13	Scania DC13
	271/202 @ 1800	394/294 @ 1800	394/294 @ 1800
	Stage V	Stage V	Stage V
	17510	16060	19615
	13780	11795	15125
	14195	12755	14435
	14320	14155	16195
	3400	3340 - 3900	3340 - 3900
	3475	3910	4070

MATERIAL HANDLERS

Material Handler		DX230WMH-7 Gooseneck Arm	DX230WMH-7 Straight Arm
Operating weight	kg	24017	24317
Travel speed	km/h	4 - 9 - 20	4 - 9 - 20
Engine model	-	Develon DL06V	Develon DL06V
Power (SAE J1995)	hp/kW @ rpm	189/141 @ 1900	189/141 @ 1900
Emission standard	-	Stage V	Stage V
Max. bucket pin height	mm	11400	11600
Max. working reach	mm	10000	10000
Max. working depth	mm	4300	4000
Boom Length	mm	6100	6100
Arm Length	mm	4200	4000
Min. swing radius	mm	2700	2700
Elevating height	mm	2500	2500

Material Handler		DX250WMH-7 Gooseneck Arm	DX250WMH-7 Straight Arm
Operating weight	kg	25397	25672
Travel speed	km/h	4 - 9 - 20	4 - 9 - 20
Engine model	-	Develon DL06V	Develon DL06V
Power (SAE J1995)	hp/kW @ rpm	189/141 @ 1900	189/141 @ 1900
Emission standard	-	Stage V	Stage V
Max. bucket pin height	mm	12100	11900
Max. working reach	mm	10700	10400
Max. working depth	mm	4700	4100
Boom Length	mm	6500	6500
Arm Length	mm	4500	4000
Min. swing radius	mm	2700	2700
Elevating height	mm	2500	2500

MONOLITHIC ARM

Demolition Arm		DX140DM-7
Operating weight	kg	22500
Maximum swing speed	rpm	10.13
Engine model	-	Develon G2 D34
Power SAE J1995	hp/kW @ rpm	115/86 @ 1800
Emission standard	-	Stage V
Number of cylinders	-	4
Max tool weight	kg	1450
Pin height	mm	16100
Overall length	mm	2859
Overall length (without arm)	mm	4130
Width superstructure	mm	2590
Variable undercarriage width	mm	2520/3700
Overall height	mm	3020
Shoe width	mm	500

INTERCHANGEABLE ARM

		DX140DM-7 Demolition	DX140DM-7 Digging
Operating weight	kg	22300	21300
Maximum swing speed	rpm	10.13	10.13
Engine model	-	Develon G2 D34	Develon G2 D34
Power SAE J1995	hp/kW @ rpm	115/86 @ 1800	115/86 @ 1800
Emission standard	-	Stage V	Stage V
Number of cylinders	-	4	4
Max GP Bucket	m3	-	0.76
Pin height (without extension)	mm	14100	-
Pin height (with extension 2m)	mm	16100	-
Max tool weight	kg	1450	0.76 (m3)
Pin height	mm	16100	8100
Overall length	mm	3773	3773
Overall length (without arm)	mm	4304	4304
Width uperstructure	mm	2327	2327
Variable undercarriage width	mm	2520/3700	2520/3700
Overall height	mm	2859	2859
Shoe width	mm	500/600	500

DEMOLITION

Demolition		DX245DM-7 HRD	DX245DM-7 Digging
Operating weight	kg	30800	28900
Travel speed	km/h	3.0 - 5.5	3.0 - 5.5
Engine model	-	Develon DL06P	Develon DL06P
Power (SAE J1995)	hp/kW @ rpm	173/129 @ 1800	173/129 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	12900	8170
Pin depth	mm	N/A	4785
Pin height	mm	18070	8155
Overall length	mm	11460	9590
Width superstructure	mm	2540	2540
Variable undercarriage width	mm	2540 ~ 3740	2540 ~ 3740
Overall height	mm	3150	3150

Demolition		DX380DM-7 HRD	DX380DM-7 Digging
Operating weight	kg	47400	44800
Travel speed	km/h	3.0 - 5.4	3.0 - 5.4
Engine model	-	Scania DC09	Scania DC09
Power (SAE J1995)	hp/kW @ rpm	327/240 @ 1800	327/240 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	14500	10200
Pin depth	mm	N/A	5500
Pin height	mm	23000	9200
Overall length	mm	15200	11285
Width superstructure	mm	2990	2990
Variable undercarriage width	mm	2970 ~ 4370	2970 ~ 4370
Overall height	mm	3148	3148

DEMOLITION

Demolition		DX530DM-7 HRD	DX530DM-7 Digging
Operating weight	kg	60500	56800
Travel speed	km/h	3.1 - 5.5	3.1 - 5.5
Engine model	-	Scania DC13	Scania DC13
Power (SAE J1995)	hp/kW @ rpm	394/294 @ 1800	394/294 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	16500	10300
Pin depth	mm	N/A	5965
Pin height	mm	27500	9690
Length	mm	18500	12230
Width	mm	2990	2990
Variable undercarriage width	mm	2970 ~ 4370	2970 ~ 4370
Height	mm	3360	3360

Demolition		DX530DM-7 HRD (Special version)	DX530DM-7 Digging (Special version)
Operating weight	kg	70500	63000
Travel speed	km/h	3.1 - 5.5	3.1 - 5.5
Engine model	-	Scania DC13	Scania DC13
Power (SAE J1995)	hp/kW @ rpm	394/294 @ 1800	394/294 @ 1800
Emission standard	-	Stage V	Stage V
Pin reach	mm	18000	10300
Pin depth	mm	N/A	5965
Pin height	mm	31000	9690
Length	mm	22300	12230
Width	mm	2990	2990
Variable undercarriage width	mm	2970 ~ 4370	2970 ~ 4370
Height	mm	3360	3360

DOZER

Model		DD130-7
Operating weight	kg	14.500
Engine power	hp/kW @ rpm	157/2200
Max. traction force	t	22

Travelling Performance, Travelling Speed	km/h	9
Overall lenght with blade & Ripper	mm	6030
Overall lenght with blade only	mm	5035
Overall width (Blades width)	mm (LGP2/LGP1/XL)	3105/3345/ 3655
XL-Version with 560-mm-shoes	cm2	33818
LGP1-Version with 710-mm-shoes	cm2	42875
LGP2-Version with 760-mm-shoes	cm2	45895

DEVELON
DD 130

ATTACHMENTS

DO IT ALL!

Range of Develon Buckets, Breakers, Quick Couplers, Pallet Forks and more...
For: Develon wheel loaders, crawler and wheeled excavators.



EQUIPMENT INFORMATION

Considering purchasing equipment? View the brochures that you are interested in, compare the specifications of the equipment, and request a quotation from your local dealer.

ONLINE PARTS SHOP

Helps you purchase quality-proven genuine parts quickly. You can order quickly and easily the parts you need by searching for the right parts for your equipment.

MY MACHINE

You can check all equipment data and maintenance costs easily and conveniently via the easy-to-use Dashboard.

CUSTOMIZED SERVICE

Receive push notification alerts when equipment requires attention and manage your machine effecti-vely with a checklist according to the product life cycle. You can request service directly and check the progress.

SOCIAL MEDIA WALL

Enjoy the moment with Develon Construction equipment!

DISCOVER MORE:

DEVELON Infracore Europe s.r.o.
IBC - Pobřežní 620/3, 186 00 Praha 8-Karlín
Czech Republic

©2023 DEVELON D4600683-EN (03-23)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice.
Specification(s) for your individual Develon equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Develon units may show other than standard equipment.

DEVELON